

FORM PCT 1390  
REV: 5/93

U S DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NO  
EBERLE (PCT)TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371

U S APPLICATION NO (if known, see 37 CFR 1.5)

09/673468

INTERNATIONAL APPLICATION NO.  
PCT/DE00/00447INTERNATIONAL FILING DATE  
FEBRUARY 17, 2000PRIORITY DATE CLAIMED  
FEBRUARY 17, 1999

## TITLE OF INVENTION

ELECTRIC MACHINE (Elektrische Maschine)

## APPLICANT(S) FOR DO/EO/US

WERNER EBERLE

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371 (f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(l).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
  - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau)
  - b. ☐ has been transmitted by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
  - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ have been transmitted by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has **NOT** expired.
  - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

## Items 11. to 16. below concern other document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A **FIRST** preliminary amendment.  
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

Designation of Inventors

3 SHEETS OF FORMAL DRAWINGS

APPLICATION NO (if known, see 37 CFR 1.5)

09/673468

INTERNATIONAL APPLICATION NO  
PCT/DE00/00447ATTORNEY'S DOCKET NO  
EBERLE (PCT)☒ The following fees are submitted:**Basic National Fee (37 CFR 1.492(a)(1)-(5)):**

Search Report has been prepared by the EPO or JPO.....\$860.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)

.....\$710.00

Neither international preliminary examination fee paid (37 CFR 1.82) nor  
international search fee (37 CFR 1.445(a)(2)) paid to USPTO.....\$1000.00International preliminary examination fee paid to USPTO (37 CFR 1.482)  
and all claims satisfied provisions of PCT Article 33(2)-(4).....\$100**ENTER APPROPRIATE BASIC FEE AMOUNT =**

\$860.00


Surcharge of \$130.00 for furnishing the oath or declaration later than \_\_\_\_ 20 \_\_\_\_ 30  
months from the earliest claimed priority date (37 CFR 1.492(e)).

Claims	Number Filed	Number Extra	Rate		
Total Claims	17 - 20 =	- 0 -	X \$18.00	\$	
Independent Claims	1 - 3 =	- 0 -	X \$80.00	\$	
Multiple dependent claim(s) (if applicable)			+ \$270.00	\$	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				\$	
Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).				\$	
<b>SUBTOTAL =</b>				\$860.00	
Processing fee of \$130.00 for furnishing the English translation later than ____ 20 ____ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
<b>TOTAL NATIONAL FEE =</b>				\$860.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				See cover sheet attached to assign \$ to be charged to Deposit Acct	
<b>TOTAL FEES ENCLOSED =</b>				\$860.00	
				Amount to be: refunded	\$
				charged	\$

- a. ☒ A check in the amount of \$860.00 to cover the above fees is enclosed.
- b. \_\_\_\_ Please charge my Deposit Account No. 03-2468 in the amount of \$\_\_\_\_\_ to cover the above fees. A duplicate copy of this sheet is enclosed.
- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment, to Deposit Account No. 03-2468. A duplicate copy of this sheet is enclosed.


**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:  
COLLARD & ROE, P.C.  
1077 Northern Boulevard  
Roslyn, New York 11576-1696  
(516) 365-9802

  
Signature  
Edward R. Freedman  
Reg. No. 26,048

Express Mail No. **EL 621 999 014 US**  
Date of Deposit October 17, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10, on the date indicated above, and is addressed to the Ass't. Commissioner for Patents, Washington, D.C. 20231

  
Lisa L. Vulpis

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT OR PATENTEE: WERNER EBERLE  
SERIAL OR PATENT NO.: PCT/DE00/00447  
FILED OR ISSUED: FEBRUARY 17, 2000  
GROUP:  
TITLE: ELECTRIC MACHINE

## SMALL ENTITY DECLARATION

☒ [ X ] FOR INDEPENDENT INVENTOR(S)

As a below-named inventor, I hereby declare that I am an independent inventor who (1) has not assigned, granted, conveyed, or licensed, and (2) is under no obligation under contract or law, to assign, grant, convey, or license, any rights in the invention, to any person who could not likewise be classified as an independent inventor if that person had made the invention, or to any concern which would not qualify as a small business concern or a nonprofit organization, as defined in 37 CFR 1.9(c).


☐ [ ] FOR SMALL BUSINESS CONCERN

I hereby declare that \_\_\_\_\_ is a business concern which qualifies as a small business concern as defined in § 1.9(d) - namely, (1) whose number of employees, including those of its affiliates, does not exceed 500 persons; and (2) which has not assigned, granted, conveyed, or licensed, and is under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who could not be classified as an independent inventor if that person had made the invention, or to any concern which would not qualify as a small business concern or a nonprofit organization under this section; and that the exclusive rights to the invention have been conveyed to and remain with the above-identified small business concern.

I further declare that all statements made herein of my own knowledge are true and all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful, false statements and the like, so made, are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful, false statements may jeopardize the validity of the patent application or any patent issuing thereon.

Each of the undersigned hereby grants the firm of **COLLARD & ROE, P.C.**, 1077 Northern Boulevard, Roslyn, New York 11576, U.S.A., the power to insert in this Small Entity Declaration any further identification which may be necessary or desirable to comply with the rules of the U.S. Patent and Trademark Office for filing and acceptance of this Declaration.

INVENTOR(S):

X   
Name: Werner Eberle

Date: 27 November 2000

ELECTRICAL MACHINE

The invention relates to an electrical machine with a single-pole winding with a structure substantially comprising two bodies, whereby at least one of said bodies has a layered structure in the form of a laminated sheet-iron plate and at least one of said bodies is assembled in a segmented manner as a receiving body substantially comprising at least two carrier segments; whereby each of said carrier segments, which are structured layered on their own as well, is suitable for receiving in an operationally fixed manner at least two winding carriers in suitable cavities; and whereby said winding carriers each can be wound separately.

Such an electrical machine is known from DE-A 1 181 312. The layered and at the same time segmented structure of a machine body is expected to assure adequate venting of the electrical machine by making individual segments of such a laminated sheet plate shorter, so that additional venting channels are opened in this way.

An electrical machine that is structured in a similar way is known from German patent specification DE 196 43 561.

It is known since a long time in connection with electrical machines to make provision for single-pole

windings for the purpose of avoiding overlapping of conductors in order to achieve a particularly compact winding. The problem in conjunction with such single-pole windings is that due to the constant width of the pole cores, which is desirable for making the flow density more uniform, an overall unsatisfactory groove filling factor is obtained as a consequence of the radially outwardly expanding grooves for receiving the windings.

Another problem of electrical machines is that in the event of a conductor fracture, either the rotor has to be replaced as a whole, or said component has to be completely newly rewound.

Therefore, for avoiding such drawbacks, an electrical machine is proposed in DE-PS 196 43 561 whose rotor has a structure substantially comprising two different types of segments. The one segment is a completely pre-wound, finished T-segment, which advantageously may be wound with the help of a machine, and the other segment is an X-segment. According to the instruction of said patent specification, the rotor or stator of an electrical machine can be manufactured in a simple way by plugging the respective segments together to obtain a rotor or a stator. In this connection, the pole segments are connected to each other by means of thin holding pins to obtain a rotor or a stator.

The advantage of this known solution lies in that it is possible to use pole segments that are already completely pre-wound and finished, and in particular wound with a machine. Such pole segments can be employed in conjunction with interior rotors, external rotors, or even in connection with axial-flow machines and linear motors.

However, in the course of practical realization of such an electrical machine it was found that it is difficult to assemble an armature or rotor from said pole segments. Because of the manufacturing tolerances achievable in connection with such components it was not possible to assemble a circular machine element. It was accordingly not possible to assemble the armature or rotor of an electrical machine from the pole segments described above.

Furthermore, it is not possible to simply reduce the number of the individual segment in order to facilitate the assembly because said number has a direct relation to the pole division or pole number desired in a given case for the respective electrical machine. Moreover, the aforementioned segmentation of a soft-magnetic body of the electrical machine leads to substantial variations in the width of the air gap, which is not acceptable especially in conjunction with electrical machines operating at high speeds. Furthermore, an air gap width varying beyond the periphery of the rotor leads to scatter loss impairing the efficiency,

as well as to possible variations in the synchronism and output of the electrical machine.

Therefore, the invention is based on the problem to open up the widest possible field of application for the advantageous structure of an electrical machine comprising at least one body with a segmented structure.

Said problem is solved with an electrical machine as defined in the introductory part of the independent claim in that the carrier segments of the electrical machine are manufactured in such a way that the winding carriers are equally well usable for linear motors and rotational machines. This permits a manufacture according to the modular principle. Furthermore, the winding carriers are secured in a detachable manner, so that individual winding carriers can be replaced in the event of a conductor fracture or other defects. Furthermore, the electrical machine can be fitted with winding carriers depending on the power density desired in the given case. The modular construction thus permits an exact adaptation to the installation space or the requirements in the given case, first of all, whereby the fitting of the machine, furthermore, can be exactly adapted to said parameters. The present machine accordingly can be varied in almost any desired way with nearly no change in its manufacture.

According to said solution as defined by the invention, a distinction is made between carrier segments for building up a receiving body and winding carriers by segments. A carrier segment as defined by the invention is in each case suitable for receiving a plurality of winding carriers, at least two winding carriers.

The carrier segments, in each case decoupled from the given pole pitch, can be dimensioned in this manner in such a way that they cover in each case more than one pole pitch of the electrical machine. In conjunction with rotating electrical machines it is thus possible to assemble the rotor or stator from two, four, six, eight or another selectable number of carrier segments. Said number, however, should be as low as possible for manufacturing reasons.

The selection of the number of carrier segments to be assembled in a given case is, in this connection, entirely independent of the pole number of the respective electrical machine because only up to a defined number of winding carriers - said number being determined by the size of the carrier segment - can be inserted in the carrier elements.

As opposed to the prior art, the deviations from the ideal measure in the dimensions of the individual components required for the assembly of the machine body, such deviations being unavoidable within the framework of the



usual manufacturing tolerances, cannot add up in such a way that, as the final result, the machine body cannot be assembled. The number of carried segments used is for that purpose selected independently of the pole number of the machine and depending on the manufacturing accuracy and tolerances in a way such that the respective body of the electrical machine can be safely assembled.

Advantageous developments of the instruction as defined by the invention are specified according to the following dependent claims.

Owing to the fact that according to claim 2, each carrier segment by itself completely forms the respective cavities, an easier assembly of the machine is assured than if corresponding cavities were formed also between the segments.

The modular structure of the machine becomes even more efficient if the machine can be assembled from pre-fabricated laminated sheet-iron plates.

According to an advantageous development of the invention, the winding carriers are already completely wound before they are inserted in the respective receiving body. The winding carriers can be wound separately and with the

help of machines in particular by employing the flyer technique.

The winding as such, but also the operationally fixed support of the windings is facilitated in that the winding carriers each have pronounced coil heads. Producing the winding carriers in the form of single-pole windings permits the formation of flat coil heads and thus extremely compact designs of machine construction.

The winding carriers can be connected with the respective receiving bodies in a simple manner by means of plug pins in a detachable and operationally fixed manner.

It may be necessary in conjunction with multiphase machines to arrange a plurality of separate windings on one single winding carrier. This, too, is substantially facilitated by the fact that the winding carriers can be pre-wound separately.

An embodiment of the winding carrier that is particularly advantageous with respect to both its manufacture and operation is specified according to claim 7.

Because of the special form of the winding carrier and the receiving body it is possible also with such a structure of the machine to form an at least nearly closed surface

vis-a-vis the air gap. This assures uniform flow-through and thus the synchronism of the machine.

It is alternatively or additionally possible to secure each winding carrier by means of a projection that engages a corresponding guide groove of the receiving body.

A plurality of distinguishable windings can be advantageously arranged on the winding carrier.

According to a further development of the invention, the pole shanks are wound with a flat wire. As opposed to round wires such a flat-wire winding avoids the possible formation of cavities in the space of the grooves. The smooth-edged space of the groove, which preferably has a rectangular cross section, can be optimally filled in this way. A high groove filling factor increases the degree of efficiency of the respective electrical machine.

Owing to the fact that the receiving bodies each are structured as laminated sheet-iron plates in a way such that the individual layers are arranged offset, leaving free the cavity provided for receiving the completely wound, i.e. the finished pole shank of the winding carrier, the carrier segments are structured as a whole as laminated sheet-iron plates each having the highest density.

Avoiding additional air gaps between the adjacent carrier segments, the cogging achieved in this way substantially increases the possible flow through the respective electrical body because of the increased relative permeability constant  $\mu_r$ . Furthermore, the mechanical strength of the receiving body so clogged is increased.

According to a further improvement of said advantageous further development, the thickness of the laminated sheet plates employed for building up the receiving bodies can be freely selected depending on the machine output desired in the given case. The winding carriers to be pushed in remain unaffected thereof up to a certain limit.

A further increase of the efficiency of the electrical machine so structured is obtained in that the individual receiving bodies can be build up from grain-oriented transformer sheets, whereby the orientation is not lost even beyond the periphery of the electrical machine because of the segmented arrangement.

According to a further development of the invention it is possible within the framework of the latter to build up a compensated electrical machine by structuring the receiving body in a way such that receiving bodies can be pushed in on both sides, i.e. disposed both radially on the inside and

radially on the outside, or disposed inside and outside in conjunction with linear motors.

Owing to the modular structure of the machine and the fact that it can be adapted at the same time in almost any desired way to the power density required in the given case it is possible to employ the machine anywhere where perfect adaptation to the available installation space is required. If it is designed in the form of a linear motor, for example, it can be mounted as a direct drive on a closed handling axle instead of attaching an additional linear motor next to the handling axle. A completely closed design offers many advantages especially in an aggressive environment.

According to claim 17, the electrical machine as defined by the invention can be advantageously employed both as a linear motor and a motor with an interior or external rotor. It is likewise possible also to build up synchronous, asynchronous, permanently excited or electronically commuted electric machines or direct drives. Furthermore, if the winding carrier is wired accordingly, the electrical machine as defined by the invention can be build up also in a simple way as a compensated motor.

The invention is explained in greater detail in the following with the help of a number of exemplified embodiments shown by cutouts in the drawing. In the drawing,

FIG. 1 shows by a cross sectional view a cutout of a rotational primary component of an electrical machine with two carrier segments for building up such a primary component.

FIG. 2 is a view of a detail of a carrier segment with a winding carrier associated with said carrier segment.

FIG. 3 shows a carrier segment with inserted winding carriers for a rotational primary component.

FIG. 4 shows a cross sectional view of a carrier segment with inserted winding carriers for a linear motor.

FIG. 5 shows a cross sectional view of a receiving body with inserted winding carriers for building up a compensated linear motor.

FIG. 6 shows a cross sectional view of a modified winding carrier.

FIG. 7 is a cross sectional view of a correspondingly modified carrier segment for a linear motor; and

FIG. 8 is a cross sectional view of a correspondingly modified carrier segment for a rotational machine.

FIG. 1 shows the cutout of a rotational primary component of an electrical machine. The cutout shows about  $60^\circ$  of a full circle of the primary component 1. Said range of the primary component 1 is substantially assembled from the two carrier segments 2 and 3, which each are suitable for receiving the winding carriers 4, which are already completely wound and finished. In the present exemplified embodiment, the two carrier segments 2 and 3 extend over a range of approximately  $30^\circ$ , so that the entire primary component can be assembled from 12 of such carrier segments 2 and 3.

The number of carrier segments 2 and 3 adding up to a complete, in the present case rotational primary component can be selected in any desired way irrespective of the desired pole pitch by dimensioning the carrier segments 2 and 3 accordingly. The carrier segments 2 and 3 are substantially build up from tooth-shaped, grain-oriented transformer sheets, whereby provision is made for the cavities 6 located between the individual teeth 5 of the transformer sheets for receiving the winding carriers 4. The winding carriers 4 are pushed with their punch-like pole shanks 7 into the cavities 6 in a way such that the cavity 6

remaining on both sides of the pole shanks 7 represents the groove for the respective single-pole windings.

Like the carrier segments 2 and 3, the pole shanks 7 have recesses for receiving the plug pins 10 that serve for connecting the winding carriers 4 with the respective carrier segment 2 or 3.

The pole shanks 7 are pre-wound by means of a machine. They are preferably provided with a flat wire winding produced by the flyer technique. Said winding encloses the pole shank 7 as completely as possible, on the one hand, and fills the remaining hollow space or cavity 6 as completely as possible. The flat wire winding proposed in the present exemplified embodiment is suited to optimally filling the respective hollow spaces 6.

The cavities 6 are finally sealed by the coil head 11 of the winding carrier 4. Within the framework of the invention it is possible also that the hollow spaces 6 are sealed by the coil heads 11 only partially, if necessary.

As mentioned before, the carrier segments 2 and 3 each are produced laminated from punched, grain-oriented thin transformer sheet material. It is possible also to employ laminated sheet plates that are already pre-layered. The carrier segments 2 or 3 each are build up in such a way that



the aforementioned transformer plates are stacked up one on top of the other to form a laminated sheet plate, whereby the individual layers for building up the receiving bodies are arranged one on top of the other in such a way that each layer is offset versus the other by one pole pitch, so that a hollow space 4 remains left available in each case for receiving a winding carrier 4. By offsetting the individual layers of the plate, a cogging of the adjacent carrier segments 2, 3 is obtained in such a way that the abutting edges 12 present between the individual carrier segments 2 or 3 are clogged and almost completely closed. An overall superior flow of current through the soft-magnetic receiving body is achieved in this way.

FIG. 2 shows by a detailed view the cutout of a carrier segment 22 for a linear motor that is suitable for receiving one single winding carrier 4. The carrier segment 22 has in each case the cavities 6 for receiving the pole shank 7 of the winding carrier 4. The winding carriers 4 are in this connection pushed into the cavity 6 in a way such that the pole shanks 7 - which are provided with a flat wire winding in a way not shown here in detail - each are completely received in the hollow space 6. In a way also not here in greater detail, the winding carriers 4 each are connected with the respective carrier segment 22 in an operationally safe yet detachable way by means of a plug pin 10. The winding carrier 4 is mounted in conjunction with the carrier

segment 22 in an analogous manner for building up rotational machine bodies.

Owing to the simple installation of the winding carriers 4 in the carrier segments 2 and 3, which is particularly obvious from FIG. 2, it is possible in case of a conductor fracture or some other damage to the insulation of the winding to simply replace the affected winding carriers 4 completely. Furthermore, by equipping the carrier segments 2 or 3 with winding carriers 4 accordingly it is possible to vary in a simple manner the pole pitch or the maximally available torque of the respective electrical machine.

FIG. 3 shows a carrier segment with the inserted winding carriers 4. The winding carriers 4 are connected with the carrier segment 2 via the plug pins 10 in a detachable yet operationally safe manner. Within the yoke of the rotor on the inner circle of the carrier element 2, provision is made for the recesses 13 for receiving connecting pins not shown here in detail.

The carrier segments 2, 3 can be connected with each other by means of the recesses 13 and the aforementioned connecting pins for forming a rotational electrical receiving body.

FIG. 4 shows the analogous structure of a carrier segment 22 for a linear motor. In the present case, too, provision is made within the zone of the yoke on the inner circle of the carrier segment 12, 3 for the recesses 13 for connecting pins for the connection with the adjacent carrier element and for building up the layered stack of sheets.

According to an alternative design of the carrier segments 2, 3 or 22, compensated electrical machines can be build up according to the instruction of the invention as well.

For said purpose, the carrier segments 22 each have on both sides, i.e. on the inner side and the outer side of the machine, the hollow spaces 6 for receiving the winding carriers 4. The winding carriers 4 inserted on the one side represent compensation windings versus the winding carriers 4 pushed in on the other side. An electrical motor that is compensated as desired can be build up in this way in a simple manner.

The electrical machine is more or less compensated depending on the way in which the segmented receiving body is outfitted.

In an analogous way it is possible also to produce a rotational electrical body for building up a corresponding rotational compensated electrical machine.

FIG. 6 shows a modified embodiment of a winding carrier 4 in connection with which the pole shank 7 has a largely rectangular profile whose transverse sides each are limited by an equally legged trapezoidal element (31, 32), whereby the trapezoidal element 31 facing the air gap of the electrical machine forms the coil head, and the other trapezoidal element 32 is facing the yoke of the carrier segment. The surface of the coil head facing the air gap may be designed in this connection with a cross section in the form of a circular segment whose curvature is dependent on the given circumference of the machine. A uniform expanse of the air gap is assured in this way in conjunction with the non-wound poles of the carrier segments.

The winding carrier 4 can be identically employed for the carrier segment 33 of a linear motor according to FIG. 47 or for the carrier segment 34 of a rotational machine according to FIG. 8, whereby the basic profiles have to be adapted in each case in view of the circumference of the given machine.

An electrical machine is described according to the preceding exemplified embodiments whose armature or rotor or

whose one electrical body can be built up in the case of a linear motor in a simple way by connecting the respective carrier segments 2, 3, 22, 33, 34 in the form of modules. The mechanically pre-wound winding carriers 4 can be inserted in a simple manner in said carrier segments 2, 3, 22, 33, 34 depending on the desired pole pitch, machine capacity or compensation effect. If any of the winding carriers 4 are damaged they can be replaced in a simple way. Owing to the fact that according to the instruction of the invention, the size of the individual carrier segments 2, 3, 22, 33 or 34 is in each case entirely independent of the desired pole pitch, the individual carrier segments 2, 3, 22, 33 or 34 can be produced with the usual manufacturing expenditure in a way such that a constant with a constant width or with the required tolerances is obtained.

Furthermore, it is possible by means of the segmentation of the respective electrical body of the electrical machine, which segmentation may have to be adapted, if need be, to safely assemble the desired electrical body without having to demand compliance with manufacturing accuracies not usually required to be met in the construction of electrical machines. Even a rotational armature or stator can be manufactured and safely assembled by the advantageous segment construction described above in a simple way. The width of the air gap depending on the number of receiving bodies to be assembled remains adequately

constant in this connection over the entire circumference of the electrical body.

Said segmented-type construction permits the construction of machines with different radii, fittings and torques with always the same winding carriers 4. The application spectrum for said winding carriers 4 and thus the pieces of units to be produced are substantially increased in this way.

This leads to a further reduction of the manufacturing costs. According to the exemplified embodiments described above, the winding carriers 4 can be used even both for linear and rotating electrical bodies.

This leads to a further widening of the application spectrum and results in the desired increase of the number of units to be produced as well, at least with respect to the manufacture of the winding carriers 4 described above.

### List of Reference Numerals

- 1 Primary component
- 2 Receiving body
- 3 Receiving body
- 4 Winding carrier
- 5 Tooth
- 6 Cavity
- 7 Pole shank
- 
- 10 Plug pin
- 11 Coil head
- 12 Abutting edge
- 13 Recess
- 
- 22 Receiving body
- 31 Trapezoidal element on air gap side
- 32 Trapezoidal element on yoke side
- 33 Modified carrier segment for linear motor
- 34 Modified carrier segment for rotational machine

Claims:

1. An electrical machine with a single-pole winding substantially structured from two bodies, whereby at least one of said bodies is structured in the form of a laminated sheet plate and at least one of the bodies is assembled in a segmented form substantially from at least two carrier segments (2, 3, 22), and whereby each of said carrier segments (2, 3, 22, 33, 34) is by itself structured in a laminated way as well for receiving in an operationally safe manner at least two winding carriers (4) in suitable cavities (6), said winding carriers each being wound separately, characterized in that the winding carriers (4) are secured in a detachable manner; that the cross section of each cavity (6) of a receiving body assembled from the carrier segments (2, 3, 22, 32, 34) of a rotational electrical machine is at least approximately equal to the cross section of each cavity (6) of the receiving body of a linear electrical machine; and that the winding carriers (4) are in this way equally usable for both types of machine.

2. The electrical machine according to claim 1, characterized in that the cavity (6) for the winding carrier (4) is limited by a yoke as well as by two adjacent non-wound poles of the respective carrier segment (2, 3, 22, 33, 34).



3. The electrical machine according to claim 1 or 2, characterized in that sheet layers used for building up the winding carriers (4) and/or the carrier segments (2, 3, 22, 33, 34) are pre-configured in the form of laminated sheet plates, and that the electrical machine is at least partly assembled from said laminated plates in the form of a module construction.

4. The electrical machine according to any one of the preceding claims, characterized in that the winding carriers (4) are completely wound, preferably wound by a machine before they are mounted.

5. The electrical machine according to claim 4, characterized in that the winding carriers (4) each are designed in the form of profiled bodies with a coil head (11) and a pole shank (7).

6. The electrical machine according to claim 4 or 5, characterized in that the winding carriers (4) each are operationally rigidly but detachably connected with the respective receiving body (2, 3, 22) preferably by means by plug pins (10).

7. The electrical machine according to any one of claims 4 to 6, characterized in that the profile of the winding carrier (4) is limited on each longitudinal side by

an equally legged trapezoidal element, with an at least approximately rectangular center component being disposed between said trapezoidal components, said center component forming the pole shank (7).

8. The electrical machine according to claim 7, characterized in that the cavities (6) have a profile suitable for receiving in a form-locked manner the trapezoidal element (33), the latter pointing at the yoke of the receiving body in the operating condition, as well as for receiving the pole shank (7), whereby in the operating condition, the trapezoidal element (31) facing away from the yoke, said trapezoidal element forming the coil head (11), and the surfaces of the adjacent non-wound poles of the receiving body jointly form an at least approximately closed surface pointing at the air gap of the electrical machine.

9. The electrical machine according to any one of the preceding claims 4 to 8, characterized in that the surface of the winding carrier (4) pointing at the yoke of the receiving body is in each case provided with a projection which, in the operating condition, is in engagement with a corresponding guide groove located in the zone of the yoke of the receiving body.

10. The electrical machine according to any one of the preceding claims 4 to 9, characterized in that a plurality

of distinguishable windings are arranged at least on a part of the winding carrier (4).

11. The electrical machine according to any one of the preceding claims 4 to 10, characterized in that the winding carriers (4) are provided with a flat wire winding.

12. The electrical machine according to any one of the preceding claims, characterized in that the carrier segments (2, 3, 22, 33, 34) structured from laminated sheet plates are designed in such a way that the individual layers are arranged offset, leaving clear the cavities (6) provided for receiving the winding carriers (4), in a way such that viewed across the circumference or the length of the electrical machine, each individual layer of each carrier segment (2, 3, 22, 33, 34) is in turn structured in a segmented manner; and that the segments of the one layer are arranged offset vis-à-vis the adjacent layer, and so offset preferably by one pole pitch.

13. The electrical machine according to claim 12, characterized in that the number of sheet layers used in each case for building up the receiving bodies (2, 3, 22, 33, 34) is freely selectable depending on the machine output required in given case.

14. The electrical machine according to claim 12 or 13, characterized in that the carrier segments (2, 3, 22, 33, 34) each are build up from layers of transformer sheets punched out in the form of teeth, preferably from grain-oriented sheet material.

15. The electrical machine according to any one of claims 12 to 14, characterized in that the carrier segments (22) are provided both on the side facing the interior of the machine and on the side facing the exterior of the machine with cavities (6) distributed over the periphery for receiving winding carriers (6) for building up a compensated electrical machine.

16. The use of the electrical machine structured in a segmented manner according to claims 1 to 15, as a linear motor within a closed handling axle.

17. The use of the electrical machine structured in a segmented manner according to claims 1 to 16, as a motor with an interior or exterior rotor, linear motor, synchronous or asynchronous machine, direct drive, permanently excited machine, or as an electronically commutated machine.

## Abstract:

### 1. Electrical machine

2.1 The invention relates to an electrical machine with a single-pole winding substantially built up from bodies, whereby at least one of said bodies is structured from a number of segments at least corresponding with the number of poles of the electrical machine. It has been found in this connection that it is not possible to assemble at least the electrical bodies of rotating electrical machines in such a way.

2.2 The aforementioned problems are solved in that at least one of the inductively excitable bodies of the electrical machine is substantially assembled from receiving bodies 2, 3, whereby each receiving body 2, 3 is suitable for receiving in an operationally fixed manner at least two winding carriers 4. Said receiving bodies 2, 3 are decoupled from the given pole number or pole pitch of the machine and can be dimensioned depending on the manufacturing tolerance. Such receiving bodies 2, 3 can be assembled within out problems.

### 2.3 Single-pole winding

### 3. FIG. 1

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**ELECTRIC MACHINE**

the specification of which (check only one item below):

- ☐ is attached hereto.
- ☐ was filed as United States application  
Serial No. \_\_\_\_\_  
on \_\_\_\_\_  
and was amended  
on \_\_\_\_\_ (if applicable).
- ☒ was filed as PCT international application  
Number PCT/DE00/00447  
on FEBRUARY 17, 2000  
and was amended under PCT Article 19  
on \_\_\_\_\_ (if applicable).


I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

**PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:**

COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119
GERMANY	199 06 484.9	17 FEBRUARY 1999	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO

<b>COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY</b> (Includes Reference, to PCT International Applications)				<b>ATTORNEY'S DOCKET NUMBER</b> EBERLE-1 PCT	
I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.					
(Application Number)		(Filing Date)			
I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclose in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:					
<b>PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:</b>					
<b>U.S. APPLICATIONS</b>			<b>STATUS (Check One)</b>		
U.S. APPLICATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED	
<b>PCT APPLICATIONS DESIGNATING THE U.S.</b>					
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)			
<b>POWER OF ATTORNEY:</b> As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration numbers):					
KURT KELMAN, Registration No. <u>18,628</u> ALLISON C. COLLARD, Registration No. <u>22,532</u> ; WILLIAM C. COLLARD, Registration No. <u>38,411</u> EDWARD R. FREEDMAN, Registration No. <u>26,048</u> ; FREDERICK J. DORCHAK, Registration No. <u>29,298</u> ELIZABETH COLLARD RICHTER, Registration No. <u>35,103</u> REINE H. GLANZ, Registration No. <u>46,728</u>					
Send Correspondence to:		COLLARD & ROE, P.C. 1077 Northern Boulevard Roslyn, New York 11576		Customer No. <b>25889</b>	Direct Telephone Calls to: (name and telephone number) (516) 365-9802
2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME		SECOND GIVEN NAME
		EBERLE	WERNER		
0	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY		COUNTRY OF CITIZENSHIP
		PFORZHEIM	GERMANY <del>DEX</del>		GERMANY
1	POST OFFICE ADDRESS	POST OFFICE ADDRESS		CITY	
		VILLINGER STRASSE 8		D-75179 PFORZHEIM	
				STATE & ZIP CODE/COUNTRY	
				GERMANY	
2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME		SECOND GIVEN NAME
0	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY		COUNTRY OF CITIZENSHIP
2	POST OFFICE ADDRESS	POST OFFICE ADDRESS		CITY	
				STATE & ZIP CODE/COUNTRY	
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.					
SIGNATURE OF INVENTOR 201 			SIGNATURE OF INVENTOR 202		
DATE			DATE		